

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Identification of the substance	Hydrocarbons, C10, aromatics, <1% naphthalene
Registration number (REACH)	01-2119463583-34-0003
EC number	918-811-1
Index No	-
CAS number	64742-94-5
Additional relevant and available information	Hydrosol A200 ND Hydrosol A200 NL Hydrosol A200 ND PP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	manufacture of substances Use as an intermediate Distribution of substance Formulation & (re)packing of substances and mixtures Functional Fluids Use as a fuel Road and construction applications Use in laboratories Water treatment chemicals Polymer processing Mining chemicals Uses in Coatings Use in Cleaning Agents Lubricants Use in Oil and Gas field drilling and production operations Use in Agrochemicals Metal working fluids / rolling oils
--------------------------	--

1.3 Details of the supplier of the safety data sheet

DHC Solvent Chemie GmbH
Timmerhellstraße 28
D-45478 Mülheim an der Ruhr
Germany

Telephone: +49 (208) 9940-0
Telefax: +49 (208) 9940-150

Competent person responsible for the safety data sheet
e-mail (competent person)

Yvonne Knappe
productsafety@dhc-solvent.de

1.4 Emergency telephone number

Emergency information service

DHC Solvent Chemie GmbH
+49 (208) 9940-112

This number is only for medical emergencies.
Giftnotrufzentrale Berlin
+49 (0)30 19 240.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336
aspiration hazard	Cat. 1	(Asp. Tox. 1)	H304
hazardous to the aquatic environment - chronic hazard	Cat. 2	(Aquatic Chronic 2)	H411

Remarks

For full text of H-phrases: see SECTION 16.
 Substance with a community indicative occupational exposure limit value.

Supplemental hazard information

Supplemental hazard information.
 EUH066 Repeated exposure may cause skin dryness or cracking.

The most important adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word **Danger**

Pictograms

GHS07, GHS08,
GHS09



Hazard statements

H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P331 Do NOT induce vomiting.
 P391 Collect spillage.

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant.

Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

According to the results of its assessment, this substance is not a PBT or a vPvB.
 This material is combustible, but will not ignite readily. Vapour heavier than air, may form an explosive mixture in air at temperatures above the flashpoint. Slip hazard by spilled and leaked out product. Flowing product can create electrostatic charge, resulting sparks may ignite or cause an explosion.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Name of substance	Hydrocarbons, C10, aromatics, <1% naphthalene
Registration number (REACH)	01-2119463583-34-0003
EC number	918-811-1
CAS number	64742-94-5
Index No	-
Purity	100 %

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS
naphthalene	CAS No 91-20-3 EC No 202-049-5	< 1	Acute Tox. 4 / H302 Carc. 2 / H351 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410

For full text of abbreviations: see SECTION 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Do NOT induce vomiting. Rinse mouth with water (only if the person is conscious).

4.2 Most important symptoms and effects, both acute and delayed

Choking and suffocation risks. Narcotic effects. Deficits in perception and coordination, reaction time, or sleepiness.

4.3 Indication of any immediate medical attention and special treatment needed

none

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

carbon dioxide (CO₂), BC-powder, foam, alcohol resistant foam, water mist

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

May produce toxic fumes of carbon monoxide if burning.

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO₂)

5.3 Advice for firefighters

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Keep containers cool with water spray.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Avoid inhaling sprayed product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Remove/take off immediately all contaminated clothing and wash it before reuse.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials. - covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Recommendations

- **Measures to prevent fire as well as aerosol and dust generation**

Use only in well-ventilated areas. Use local and general ventilation.

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

- **Packaging compatibilities**

Only packagings which are approved (e.g. acc. to ADR) may be used.

Suitable materials and coatings for container/equipment: Carbon Steel, Stainless Steel, Polyester, Polytetrafluoroethylene (PTFE), Polyvinyl Alcohol (PVA)

Unsuitable Materials and Coatings for container/equipment: Butyl Rubber, Natural Rubber, Ethylene-propylene-diene monomer (EPDM), Polystyrene, Polyethylene, Polyacrylonitrile.

7.3 Specific end use(s)

See attached exposure scenarios

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
DE	hydrocarbon mixtures, C9-C15 aromatic		AGW		100		200	TRGS 900
DE	hydrocarbon mixture (RCP method)		AGW		1		2	TRGS 900
DE	Hydrocarbons, C10, aromatics, <1% naphthalene	64742-94-5	AGW		50		50	RCP method according to TRGS 900
DE	naphthalene	91-20-3	AGW	0.1	0.5	0.1	0.5	TRGS 900
EU	naphthalene	91-20-3	IOELV	10	50			91/322/EEC
UK	hydrocarbon mixture (RCP method)		WEL		250		500	EH40/2005
GB	aromatics	91-20-3	WEL		500			EH40/2005
IE	naphthalene	91-20-3	OELV	10	50	15	75	S.I. No. 619 of 2001

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

Relevant DNELs/DMELs/PNECs and other threshold levels

• human health values

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	12.5 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
DNEL	151 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	7.5 mg/kg	human, oral	consumer (private households)	chronic - systemic effects
DNEL	7.5 mg/kg	human, dermal	consumer (private households)	chronic - systemic effects
DNEL	32 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
naphthalene	91-20-3	DNEL	3.57 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
naphthalene	91-20-3	PNEC	2.9 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

Technical measures and the appliance of appropriate working methods take priority over the use of personal protective equipment.

Safety and necessary control measures vary according to exposure conditions. Appropriate measures are:

Open windows, door, to allow sufficient ventilation. If this is not possible employ a fan to increase air exchange (see attached exposure scenarios).

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection.

Skin protection

• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

Short-term contact with the skin: Disposable gloves

Long-term contact with the skin: Gloves with long cuffs

Check leak-tightness/impermeability prior to use.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

- **type of material**

NBR: acrylonitrile-butadiene rubber, FKM: fluoro-elastomer

- **material thickness**

0,40 mm.

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Body protection:

Suitable protective clothing: Flame resistant clothing

Suitable safety shoes: Anti static safety shoes according to EN 345 S3

Respiratory protection

For activities in enclosed areas at elevated temperatures of the substance, local extraction or explosion protected ventilation equipment is recommended. In case this is not sufficient for the intended use, then apply a suitable respiratory protection according to EN 140 type A or better (see exposure scenarios). .

Environmental exposure controls

Do not empty into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Colour	clear
Odour	pungent

Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	<-10 °C (ASTM D 5950)
Initial boiling point and boiling range	160 - 220 °C (ASTM D 86)
Flash point	>61 °C (ASTM D 93)
Explosive limits	
• lower explosion limit (LEL)	0.6 vol%
• upper explosion limit (UEL)	7 vol%
Vapour pressure	0.09 kPa at 20 °C
Density	0.8 - 0.95 g/cm ³ at 15 °C
Solubility(ies)	not determined
Partition coefficient	
n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	>400 °C
Viscosity	
• kinematic viscosity	0.8 - 2 mm ² /s at 20 °C (ASTM D 445)
Explosive properties	
in use, may form flammable/explosive vapour-air mixture	
Oxidising properties	none

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

9.2 Other information

Surface tension 29 - 32 mN/m (25 °C) (Wilhelmy Plate)

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure (see below "Conditions to avoid").

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge.

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Exposure route	Endpoint	Value	Species
oral	LD50	6,318 mg/kg	rat
dermal	LD50	>2,000 mg/kg	rabbit
inhalation: vapour	LC50	>4,688 mg/l/4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity (acute)

Endpoint	Value	Species	Exposure time
LL50	2 mg/l	rainbow trout (Oncorhynchus mykiss)	96 hours
EL50	3 mg/l	daphnia magna	48 hours
EL50	1 mg/l	algae	72 hours

Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

Endpoint	Value	Species	Exposure time
NOELR	0.441 mg/l	rainbow trout (Oncorhynchus mykiss)	28 d
NOELR	0.771 mg/l	daphnia magna	21 d

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Other adverse effects

Data are not available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately re-conditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

List of wastes



Proposed waste code(s) for the used product:

07 01 04x Other organic solvents, washing liquids and mother liquors

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



SECTION 14: TRANSPORT INFORMATION

14.1	UN number	3082
14.2	UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	Technical name	Hydrocarbons, C10, aromatics, <1% naphthalene
14.3	Transport hazard class(es)	
	Class	9 (miscellaneous dangerous substances and articles)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	hazardous to the aquatic environment
14.6	Special precautions for user	
	Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	
	Information for each of the UN Model Regulations	
	• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)	
	UN number	3082
	Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	Technical name (hazardous constituents)	Hydrocarbons, C10, aromatics, <1% naphthalene
	Class	9
	Classification code	M6
	Packing group	III
	Danger label(s)	9 + "fish and tree"
	 	
	Environmental hazards	yes (hazardous to the aquatic environment)
	Special provisions (SP)	274, 335, 375, 601
	Excepted quantities (EQ)	E1
	Limited quantities (LQ)	5 L
	Transport category (TC)	3
	Tunnel restriction code (TRC)	E
	Hazard identification No	90
	Emergency Action Code	3Z
	• International Maritime Dangerous Goods Code (IMDG)	
	UN number	3082
	Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	Particulars in the shipper's declaration	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Hydrocarbons, C10, aromatics, <1% naphthalene), 9, III
	Class	9
	Marine pollutant	yes (hazardous to the aquatic environment)
	Packing group	III

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

Danger label(s)  Special provisions (SP) Excepted quantities (EQ) Limited quantities (LQ) EmS Stowage category • International Civil Aviation Organization (ICAO-IATA/DGR) UN number Proper shipping name Class Environmental hazards Packing group Danger label(s)  Special provisions (SP) Excepted quantities (EQ) Limited quantities (LQ)	9 + "fish and tree" 274, 335, 909 E1 5 L F-A, S-F A • International Civil Aviation Organization (ICAO-IATA/DGR) 3082 Environmentally hazardous substance, liquid, n.o.s. 9 yes (hazardous to the aquatic environment) III 9 + "fish and tree" A97, A158, 274 E1 30 kg
---	---

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

- **2012/18/EU (Seveso III)**

No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200	500	57)

Notation

57) Hazardous to the Aquatic Environment in category Chronic 2.

- **Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)**

VOC content 100 %

- **Directive on industrial emissions (VOCs, 2010/75/EU)**

VOC content 100 %

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has been carried out.

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
91/322/EEC	Commission Directive on establishing indicative limit values by implementing Council Directive 80/1107/EEC
Acute Tox.	acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW	workplace exposure limit
Aquatic Acute	hazardous to the aquatic environment - acute hazard
Aquatic Chronic	hazardous to the aquatic environment - chronic hazard
Carc.	carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	indicative occupational exposure limit value
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
RCP	reciprocal calculation procedure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
S.I. No. 619 of 2001	Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001
STEL	short-term exposure limit
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	time-weighted average
VOC	Volatile Organic Compounds

Hydrocarbons, C10, aromatics, <1% naphthalene

Version number: GHS 1.0

Revision: 25.02.2016

Abbr.	Descriptions of used abbreviations
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- See attached exposure scenarios

http://www.dhc-solvent.de/dhc_sdbreach.html

http://www.dhc-solvent.de/en/dhc_sdbreach.html

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).
International Maritime Dangerous Goods Code (IMDG).
International Air Transport Association (IATA).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H302	harmful if swallowed
H304	may be fatal if swallowed and enters airways
H336	may cause drowsiness or dizziness
H351	suspected of causing cancer
H400	very toxic to aquatic life
H410	very toxic to aquatic life with long lasting effects
H411	toxic to aquatic life with long lasting effects